

The SEMATECH Berkeley MET & DCT: a quest for 14-nm half-pitch in chemically amplified resist, OOB contrast of EUV resists, and 6.x-nm lithography

Christopher N. Anderson, Lorie Mae Baclea-An, Paul E. Denham, Kenneth A. Goldberg, Michael S. Jones, Brittany McClinton, Ryan Miyakawa, Patrick P. Naulleau, Seno Rekawa, and Nathan S. Smith
Lawrence Berkeley National Laboratory, Center for X-ray Optics, Berkeley, CA.

Hiroki Nakagawa and Ken Maruyama
JSR Micro, Inc. Sunnyvale, CA

In August 2011, the SEMATECH Berkeley Microfield Exposure Tool (BMET) introduced a reticle that is optimized for pseudo phase-shift-mask (pseudo-PSM) imaging, providing early access to an aerial image approaching 12-nm half-pitch with contrast above 60%. In this paper we report on a new champion chemically amplified (CA) resist and characterize several other high-performing CA EUV resists from 16-nm down to 12-nm half pitch, using the pseudo-PSM technique.

In September 2011, out-of-band (OOB) capabilities were added to the SEMATECH Berkeley Dose Calibration Tool (DCT) enabling the OOB sensitivity and OOB contrast of EUV resists to be measured. In this paper we report on the OOB sensitivity and OOB contrast of champion CA EUV resists and discuss the correlation between OOB contrast and the effects of OOB radiation during EUV exposure on patterning performance. In addition, we will report on the absolute sensitivity and contrast of several commercially available EUV resists at 6.x-nm.

Finally, we will provide an update on our progress towards building the 0.5-NA SEMATECH BMET

DISCLAIMER

This document was prepared as an account of work sponsored by the United States Government. While this document is believed to contain correct information, neither the United States Government nor any agency thereof, nor The Regents of the University of California, nor any of their employees, makes any warranty, express or implied, or assumes any legal responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by its trade name,

trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof, or The Regents of the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof or The Regents of the University of California.

This work was supported by the Director, Office of Science, of the U.S. Department of Energy under Contract No. DE-AC02-05CH11231.